

| Specification No. | Main Material | Standard Film Thickness | Maximum Temperature Limit | Characteristic | | | Main Use Examples |
|-------------------|---------------|-------------------------|---------------------------|-------------------|----------------|---------------|--|
| | | | | Anti-Adhesiveness | Anti-Corrosion | Anti-Abrasion | |
| NF-004EC | FEP | 40μm | 200℃ | ◎ | × | △ | Paint/Ink Mixing Tank, Pipe, Filter, Valve, etc. |
| NF-004ECH | FEP | 100μm | 200℃ | ◎ | × | △ | Granulator, Bag Filter, Powder Hopper, etc. |
| NF-004ECX | FEP | 50μm | 200℃ | ○ | × | ◎ | Roll, Powder Hopper, Dryer, etc. |
| NF-014EC | ETFE | 600μm | 180℃ | △ | ◎ | ◎◎ | Centrifuge, Filter, Mixing Tank, Agitation Blade, etc. |
| NF-015EC | PFA | 50μm | 260℃ | ○ | × | ○ | Powder Hopper, Dryer, etc. |
| NF-015ECX | PFA | 50μm | 260℃ | ○ | × | ◎ | Roll Only (Anti-Thrust, Anti-Abrasion) |
| NF-020EC | PFA | 300μm | 260℃ | ○ | ◎◎ | ○ | Filtration Device, Mixing Tank, Agitation Blade, Hopper, etc. |
| NF-240EC | Complex | 500μm | 200℃ | ◎ | ◎◎ | ○ | Centrifuge, Filter, Mixing Tank, Reactor Tank, Agitation Blade, etc. |